



Ausführung für Entrauchungsbetrieb 400°C/120min auf Anfrage.
Smoke-extract version 400°C/120min on request.

max. Aufnahmeleistung $P_{L,max}$
peak absorbed power [kW]

Relative Frequenzspektren
relative frequency spectrum $L_{w,rel}$ in Δ dB/Okt

n [min ⁻¹]	Flügelwinkel / pitch angle [°]												Oktavb.-Mittenfr. / Octave band mid-fr. [Hz]								
	8	10	12	14	16	18	20	22	24	26	28	30	32	63	125	250	500	1k	2k	4k	8k
720 motor	0,4	0,48	0,55	0,67	0,77	0,88	0,99	1,12	1,22	1,4	1,59	1,69	1,78	-10	-7	-5	-7	-8	-12	-18	-24
960 motor	0,95	1,13	1,30	1,59	1,83	2,08	2,35	2,65	2,89	3,32	3,78	3,96	4,21	-10	-7	-5	-7	-8	-12	-18	-24
1440 motor	3,30	3,94	4,54	5,54	6,39	7,26	8,19	9,24	10,1	11,6	13,2	13,8	14,7	-10	-12	-6	-5	-7	-10	-15	-21

Abmessungen + Zubehör Seite / Dimensions + Accessories page 158-162



3.1